SPEC SHEET XSTECH CNC ROUTER MILL

TORMACH.COM/XSTECH

The ideal machine for socially distant learning

TRAVELS			
X-Axis	8.6 in. (220 mm)		
Y-Axis	6.3 in. (160 mm)		
Z-Axis	2.4 in. (61 mm)		
SPINDLE			
Spindle Power	120 W (0.12 kW) Brushless DC		
Maximum Speed	20,000 RPM		
Spindle Taper	ER11		
Noise Level (No Load Operation)	<66 db(A)		
Repositioning Accuracy	0.004 in (0.0018 mm)		
POWER			
Power Required	Single-Phase 230 Vac, 50/60 Hz		
MACHINE SPECIFICATIONS			
Table Size	12.6 in. × 5.9 in. (320 mm × 150 mm)		
Typical System Footprint	15.4 in. × 15.7 in. (391 mm × 399 mm)		
Overall System Height	16.7 in. (424 mm)		
Typical System Weight	33 lbs. (14.9 kg)		
Maximum Table Load Weight	6.6 lb (3 kg)		

xsTECH CNC ROUTER/MILL EDUCATION PACKAGE	EDUCATION
PRICE*	\$3,495
MACHINE	
xsTECH CNC Router/Mill	1
PathPilot Touchscreen Controller / Keyboard / Mouse / Jog Shuttle / Wi-Fi Module	✓
ACCESSORIES	
Electronic Tool Setter	1
ER11 Collets	1
Carbide Cutting Tool Set (16 Pieces)	1



XSTECHrouter

HIGHLIGHTED FEATURES
Fully-Enclosed with Safety Door Switch
Tormach PathPilot® Control System with Keyboard, Mouse, Touchscreen, and Tormach Jog Shuttle
ER11 Collet Uses Popular 1/8 inch, 1/4 inch, 4 mm, or 6 mm Tool Shanks
Starter Tooling Set with WER Collets and End Mills
Integrated Tool Setter
Laser Alignment System for XY Positioning
Clamp Kit

MACHINE CONTROLLER		
	User-friendly design	
A Better User Experience PathPilot Constraints PathPilot HUB is a browser-based, full-featured PathPilot simulator, producing usable G-Code.	Support for up to 4-axis continuous machining	
	Intuitive conversational programming	
	Usable G-Code Memory: Touchscreen Controller: 8 GB	
	Built-in Dropbox™ support for seamlessly transferring programs	

First Technologies Inc.

17145 W. Bluemound Rd. Suite J-276 Brookfield, WI 53005

firsteched.com 800.787.9717

